

Medical Cylinders

SKU	Service Pressure		Water Capacity		Diameter	
	psi	bar	lbs	liters	in	mm
M24	3000	207	22.0	10.0	7.25	184.2
M32	3000	207	9.1	4.1	4.38	111.3
M20	3000	207	5.7	2.6	4.38	111.3
M12	3000	207	3.4	1.5	4.38	111.3
M7.8	3000	207	2.1	1.0	4.38	111.3
M7.5	3000	207	2.1	1.0	3.21	81.5
M265	2216	153	102.2	46.4	9.80	248.9
M150	2015	139	63.7	28.9	8.00	203.2
M122	2216	153	47.1	21.4	8.00	203.2
M90	2216	153	34.7	15.7	7.25	184.2
M60	2216	153	23.2	10.5	7.25	184.2
ME	2015	139	10.2	4.6	4.38	111.3
M22	2216	153	8.5	3.9	5.25	133.4
MD	2015	139	6.4	2.9	4.38	111.3
M9	2015	139	3.8	1.7	4.38	111.3
M7	2015	139	3.0	1.4	4.38	111.3
ML6	2015	139	2.5	1.2	4.38	111.3
M6	2216	153	2.3	1.0	3.21	81.5
M4	2216	153	1.5	0.7	3.21	81.5
M2	2216	153	0.6	0.3	2.50	63.5

Medical Cylinders

SKU	Length		Cylinder Weight		Oxygen	
	in	mm	lbs	kgs	cu ft	liters
M24	23.8	605	28.4	12.9	77	2167
M32	25.5	648	10.8	4.9	32	906
M20	16.8	427	7.3	3.3	20	566
M12	10.9	277	5.1	2.3	12	340
M7.8	7.8	198	3.9	1.8	7.8	221
M7.5	11.8	300	2.9	1.3	7.5	212
M265	51.7	1313	84.7	38.4	265	7503
M150	47.2	1198	49.2	22.3	150	4248
M122	36.2	919	40.3	17.9	122	3455
M90	32.7	830	30.4	13.7	90	2549
M60	23.1	587	22.3	10.1	60	1699
ME	25.4	645	7.8	3.5	24	680
M22	16.3	414	8.2	3.7	22	623
MD	16.7	424	5.4	2.5	15	425
M9	10.9	277	3.8	1.7	9.0	255
M7	9.1	231	3.2	1.5	7.0	198
ML6	7.9	200	2.9	1.3	6.0	170
M6	11.8	300	2.3	1	6.0	170
M4	8.7	221	1.7	0.8	4.0	113
M2	5.9	149	0.75	0.34	1.6	45

Specs

DOT-3AL & TC-3ALM designed, ISO design cylinders are available

Alloy

Manufactured from high strength aluminum alloy 6061-T6 M60 and larger supplied with 1.125-12 UNF thread, all others with. 750-16 UNF thread

Threads

M60 and larger are available with either a carrying handle or protective caps and collars

Markings

Additional markings available upon request

Finish

Standard finish brushed body w/ green (white for Canada) crown & clear paint

Graphics

Logos or labels in silkscreen or Duragrafix available upon request

Accessories

Valves installed upon request, M60 and larger are available with either a carrying handle or protective caps and collars