

# SENTRY NITROGEN REGULATORS



- **Built-In Safety** – A non-adjustable, precision relief valve in every Taprite regulator that cannot be removed or easily circumvented.
- **Fail-Safe Protection** – In case of regulator failure, the integral safety will instantly activate to protect system from overpressurization. Excess pressure vented into atmosphere.
- **Keg Security** – Pressure in keg can never exceed preset level of 55-60 psig prior to shutdown. After shutoff no additional pressure enters the system.
- **Left-Hand Threads** – High pressure ports (only) have left hand threads to prevent possible use as a low-pressure outlet.
- **Non-Removable Adjusting Screw W/ Locknut** – Designed so if turned all the way in, pressure entering system stays at safe level.
- **Nitrogen** – Widely used in the beer industry, but has also been used for dispensing wine.



Model	Description
742N	Primary Beer 0-50, 60#, NI 5/15B-CV Shutoff, 3000# Black Bonnet
742HPN	Primary Beer 0-50, 60#, NI 5/16B-DB Shutoff, 3000# Black Bonnet
742HPN-100	Primary Beer 0-50, 100#, NI 5/16B-DB Shutoff, 3000# Black Bonnet
5741PMHPNT	Primary Beer 0-120 160# NI 5/16B-CV Shutoff, 3000# Black Bonnet