

# Chlorine Gas Valves

## Parts and Accessories

### Fusible Plugs

- Manufactured in accordance with Chlorine Institute specifications and CGA S-1.1
- Materials: Brass C48500 and 165° F fusible alloy

#### Ordering Information — Fusible Plugs for Cylinder Valves

Sherwood Part Number	Inlet Thread Size	Hex Size
5853T	½"–27 NGT	7/8"

#### Ordering Information — Fusible Plugs for Ton Container Valves

Sherwood Part Number	Inlet Thread Size	Hex Size
1333-N1	¾"–14 NGT (CL)-1	1¼"
1333-N2	¾"–14 NGT (CL)-2	1¼"
1333-N3	¾"–14 NGT (CL)-3	1¼"
1333-N4	¾"–14 NGT (CL)-4	1¼"
1303-N1	1"–11½ NGT (CL)-1	1¼"
1303-N2	1"–11½ NGT (CL)-2	1¼"
1303-N3	1"–11½ NGT (CL)-3	1¼"
1301-N4	1"–11½ NGT (CL)-4	1¼"

### Yoke

- Complies with Chlorine Institute specifications and CGA V-1
- Material: Forged steel with zinc plating
- CGA 820 connection

#### Ordering Information — Yoke

Sherwood Part Number	Description	Minimum Clearance
628B	Yoke Assembly	1¼"
P628A-2	Replacement Stem	1¼"
P628A-3	Replacement Slotted Follower	1¼"

### Flex Connectors

- ¾" OD, zinc-plated copper
- Working pressure 500 psig
- Provided with CGA 660 connector nuts for non-yoke applications

#### Ordering Information — Flex Connectors

Sherwood Part Number	Connectors/Length
6414X11C	CGA 820 × CGA 820; 30 in.
6414X2C	CGA 820 × CGA 820; 4 ft.
6414C	CGA 820 × CGA 820; 6 ft.
6414X1C	CGA 820 × CGA 820; 10 ft.

# Chlorine Gas Valves

## Parts and Accessories

### High Flow Yoke Adapters

- Material: Aluminum Silicon Bronze C64210

#### Ordering Information — High Flow Yoke Adapters

Sherwood Part Number	Size
5888-6	CGS 820 x 3/8" SAE Flare
5888-8	CGA 820 x 1/2" SAE Flare
5888-D	CGA 820 x 1/2"-14 NPT (male)
5888-E	CGA 820 x 660

#### Ordering Information — Gaskets for Yoke Adapters

Sherwood Part Number	Size
P10-CLAL	Lead Outlet Gasket (.937" OD)
P10-G-T	PTFE Outlet Gasket (.937" OD)

### 5928 Charging Valve

- Material: Aluminum Silicon Bronze C64210

#### Ordering Information — 5928 Charging Valve

Sherwood Part Number	Description
5928	The 5928 valve is a modification of Sherwood's ton container valve. A chlorine adapter is soldered on the outlet to permit yoke attachment to all standard chlorine cylinder valves. A standard CGA 660 outlet connection has been machined where the cylinder inlet normally is to permit connection to the permanent chlorine charging or discharge line.

### Wrenches

- Designed for use with 1210/1214 and 1210A/1214A chlorine valves and yokes
- Material: Forged steel construction
- Size: 1/4" open end; 3/8" stem square

#### Ordering Information — Wrenches

Sherwood Part Number	Description
635	Straight Shaft
635X3	Twisted Shaft